



VX 87

In-house distribution amplifier

Frequency range US/DS	5-30/47-862 MHz
Gain DS	28-31 dB
Attenuator	0-18 dB
Equalizer	3-18 dB
Output level DS CENELEC, flat	96 dB μ V
Output level DS CENELEC, 6 dB slope	98.5 dB μ V
Output level DS EN50083-5/3.Ord	114 dB μ V
Noise figure	< 8 dB
Return path amplifier US	-2 dB
Attenuator US	-
Output level US EN50083-5/3.Ord	-
RF inputs and outputs	F-type
Operating voltage	230 VAC 50/60 Hz
Power consumption	3.0 W
Operating temperature	-20°C...+55°C
Dimensions	163x90x47 mm
EMC	CE, Class A
Legend	

*Aktive / Passive jumper

客戶服務熱線: **2729 3271**



華輝無線電行有限公司
WELFARE Electronic Component Ltd.

Tel : (852) 2729 3271 Fax : (852) 2387 6919
G/F & 1/F, Ming Chu Building, 195-201 Aplu Street
Sham Shui Po, Kowloon, Hong Kong
香港九龍深水埗鴨寮街195-201號 明珠樓地下及一樓全層



本公司持有政府認可
保安防盜牌照Typell (No.1000)