


**Universal wall outlet sockets**


**DB 05**

Loop-through socket



**DB 07**

Loop-through socket



**DB 03**

Individual socket



Frequency range	5-2400 MHz	5-2400 MHz	5-2400 MHz
<b>Thru loss 5-862 MHz</b>	2.5 dB	1.0 dB	-
<b>Thru loss 862-2400 MHz</b>	3.0 dB	1.0 dB	-
<b>Side loss TV/FM 5-862 MHz</b>	10/12 dB	14/14 dB	4.5/4.5 dB
<b>Side loss TV/FM 862-2400 MHz</b>	10/11 dB	15/15 dB	5.0/5.0 dB
<b>Return loss 40-2150 MHz, IN</b>	Cat B	Cat B	Cat B
<b>Return loss 40-2150 MHz, TV</b>	Cat C	Cat C	Cat C
<b>Isolation 5-40 MHz</b>	≥35 dB 1)	≥40 dB 1)4)	>20 dB 2)
<b>Isolation 40-862 MHz</b>	≥42 dB 1)3)	≥44 dB 1)	>20 dB 2)
<b>Isolation 862-2400 MHz</b>	≥35 dB 1)	≥40 dB 1)	>20 dB 2)
<b>Screening factor</b>	> 85 dB, Class A	> 85 dB, Class A	> 85 dB, Class A
<b>Cable connection outer/inner conductor</b>	7.5/0.8-1.3 mm	7.5/0.8-1.3 mm	7.5/0.8-1.3 mm
<b>Packing unit</b>	10 pieces, 2.45 dm <sup>3</sup>	10 pieces, 2.45 dm <sup>3</sup>	10 pieces, 2.45 dm <sup>3</sup>

客戶服務熱線: **2729 3271**



華輝無線電行有限公司  
WELFARE Electronic Component Ltd.

Tel : (852) 2729 3271 Fax : (852) 2387 6919  
G/F & 1/F, Ming Chu Building, 195-201 Aплиu Street  
Sham Shui Po, Kowloon, Hong Kong  
香港九龍深水埗鴨寮街195-201號明珠樓地下及一樓全層



Linking TECHNOLOGY·PEOPLE·SOLUTION

[www.wecl.com.hk](http://www.wecl.com.hk)



香港保安業協會會員



國際專業保安協會會員

本公司持有政府認可  
保安防盜牌照Typell (No.1000)