

Product ID: SP001

Coaxial Video Surge Protector BNC Connector



Specifications:

- BNC male to BNC female, Hi Frequency for both CCTV and CATV use
- Surge Protection Attack Time: 1 ns
 - Maximum Surge Current: 4 KV
 - Surge Life: 300 surges of 100Amps
- Normal Resistance Across Coax: 10,000 MΩ
 - Surge Resistance Approx: 0Ω
- BAND PASS: 0~1 GHZ
- Power Passing Capability 130V AC/DC, 65 Vrms at 10Amps
 - Insertion Loss: Less than 0.2 dB
 - Return Loss (75 ohms): 16dB
- Return Loss (75 ohms): 16dB
 - WEIGHT: 80g

Features:

- Performs a different function than grounding requirements.
- Protects equipment from high voltage surges from nearby lightning strikes.
- Two stage protection: under 1ns-90V, over 10ns-12V.
- Wide range of applications: CCTV/CATV system, Antenna of Television, FM receivers, video camera, monitors, multiplexers & Quad processor, VCR...etc.



華輝無線電行有限公司
WELFARE Electronic Component Ltd.
Tel : (852) 2729 3271 Fax : (852) 2387 6919
G/F & 1/F, Ming Chu Building, 195-201 Ap Liu Street
Sham Shui Po, Kowloon, Hong Kong
香港九龍深水埗鴨寮街195-201號明珠樓地下及一樓全層



本公司持有政府認可保安防盜牌照Typell (No.1000)

www.wecl.com.hk