

# Video Accessories

## Color video door stations

- For KC-1MRD & KC-1GRD

- For KB-3MRD

- For KC-DAR & KB-DAR

**New**



**KC-DAR**  
w/TILT camera

**New**



**KB-DAR**  
w/TILT camera




**KA-DGR PANEL**  
Stainless steel panel  
(panel only)


### KC, KB Series Color video door stations

- Employs 1/4 inch color CCD camera.
- Tilt controlled camera.
- INSTANT ON audio & image of door upon CALL button pressed.
- White LED illumination auto turns on.
- Locator LED backlit on CALL button.
- Use parallel cable, vinyl jacketed, PE insulation.



**KC-DAR  
KB-DAR**



**KA-DGR PANEL**



### Image view area (\*marked figures are approximate)



### Specifications

Power source	Max. DC 22V approx. in operation. DC 12V approx. standby. Supplied by inside master.	
Consumption	Max. 350mA approx. 4mA approx. standby.	
Communication	Press CALL button, sounding chime at inside stations. Instantly talk. After master replies, communicate handsfree.	
Image view area	Approx. 60cm Horiz., 111~235cm Vert. at 130cm high & at 50cm from camera.	
Night viewing	White LED projected up to 30cm from camera. The background scene beyond 30cm can not be seen.	
Wiring	2 parallel wires to door, non-polarized.	
Distance	0.65mmø	1.0mmø
• Master to door	50m	100m

### System components

SYSTEM (MASTER)	DOOR STATION MODELS		
	NO.	Plastic panel	Stainless steel panel only
KC-1MRD	1	KC-DAR	KA-DGR PANEL
KC-1GRD	1	KC-DAR	KA-DGR PANEL
KB-3MRD	3	KB-DAR	KA-DGR PANEL