



## DWM-880/DWM-881/DWR-882

This state of the art wireless system is ideal for home and office use. Designed to ensure straightforward installation and effortless operation, our unique wireless technology delivers peak, high-speed performance for top audio quality.

### DWM-880 Digital Wireless Handheld Microphone

**Carrier Frequency:** 2404MHz-2476MHz

**Transmitting Power:** 10dBm(±2dBm)

**Capsule:** Dynamic

**Polar Pattern:** Supercardioid

**Impedance:** 600Ω

**Frequency Response:** 80Hz-12000Hz


**Power Supply:** Two AA batteries

**Battery Life:** Approx. 26 hours (Alkaline Battery)

**Dimension (mm):** ø53 x 222.7

**Weight (without Batteries):** 120 ± 10g

**Current Consumption:** 90mA



### DWM-881 Bodypack Digital Wireless Transmitter

**Carrier Frequency:** 2404MHz-2476MHz

**Transmitting Power:** 10dBm(±2dBm)

**Frequency Response:** 30-18000Hz

**Current Consumption:** 95mA

**Power Supply:** Two AA batteries

**Battery Life:** Approx. 26 hours (Alkaline Battery)

**Dimension (mm):** 62(L)×28.5(W)×89.3(H)

**Weight (without Batteries):** 50 ± 5g

### DWR-882 Digital Wireless Receiver

**Power Consumption:** 7.5W

**Receiving Sensitivity:** -78dBm

**Volume Adjusting Range:** 0-20dB

**Output Jack:** ø6.3mm Mono Female Jack

**Latency Time:** <20ms

**Audio Quality:** 38.4KHz / 16bits

**Dimension (mm):** 221.2 ± 3(L) × 132.6 ± 3(W) × 43.7 ± 3(H)

**Weight:** 550 ± 50g



## DW-25T/DW-25R

Our advanced 2.4GHz digital wireless technology offers dependably superior performance at all karaoke events. This set features a self-adjusting wireless range to conveniently match the size of the venue and prevent interference, while its rugged metal construction ensures years of reliable use.

### DW-25T

**Carrier Frequency:** 2,403G Hz-2,478G Hz

**Transmitting Power:** 10dBm

**Capsule:** Dynamic

**Polar Pattern:** Supercardioid

**Frequency Response:** 80Hz-12000Hz

**Impedance:** 600Ω

**Power Supply:** Two AA batteries

**Dimension (mm):** ø54.4 x 258.5(L)

**Weight (without Batteries):** 380 ± 10g

**Current Consumption:** 100mA

### DW-25R

**Power Consumption:** 7.5W

**Receiving Sensitivity:** -82dBm

**Volume Adjusting Range:** 0-20dB

**Output Jack:** ø6.3mm Mono Female Jack

**Latency Time:** <13ms

**Audio Quality:** 44.1KHz / 16bits

**Rated Output Power:** 750mV (THD=10%)

**Dimension (mm):** 210(L) × 182(W) × 105(H)

**Weight:** 800 ± 50g