

Mini Amplifier



- MA-50** 20W(rms) Mini Amplifier
- 2 Microphone & 1 Aux Input
 - Low Impedance Output (4~8Ω)
 - Built-in Siren Generator
 - Power Source: DC12V ~ 24V
 - Dimensions: 160W x 48H x 160Dmm



- MA-22** 20W(rms) Mini Amplifier
- 2 Microphone & 1 Aux Input
 - Low Impedance Output (4~8Ω)
 - Power Source: AC115V/230V
 - Dimensions: 220W x 55H x 160Dmm



Built-in Intercom Function
Between External Speaker

- MPA-30** 20W(rms) Amplifier/Intercom
- Built-in Intercom Function
 - 1 Microphone & 1 Aux Input
 - Low Impedance Output (4~8Ω)
 - Built-in Siren Generator
 - Power Source: DC12V or 24V
 - Dimensions: 160W x 48H x 160Dmm



- MA-20** 20W(rms) Classroom Amplifier
- 2 Microphone & 1 Aux Input
 - Built-in Priority Function (Mic.1)
 - Low Impedance Output (4~8Ω)
 - Applicable to Dynamic or Condenser Mic.
 - Power Source: AC220V
 - Dimensions: 292W x 190H x 65Dmm

Speaker Selector



19" Standard Rack-Mount

- MPS-1601**
- 16 Zone Speaker Outputs
 - All/Groups/Zone Selection
 - Built-in Monitor Speaker
 - Dimensions: 482W x 52H x 352Dmm



- MPS-801**
- 8 Zone Speaker Outputs
 - All/Zone Selection
 - Built-in Monitor Speaker
 - Dimensions: 310W x 52H x 175Dmm



19" Standard Rack-Mount

- MPS-1602**
- 16 Zone Speaker Outputs
 - All/Groups/Zone Selection
 - Remote Function For All Selection
 - Built-in Monitor Speaker With Volume
 - Power Source: DC24V
 - Dimensions: 482W x 52H x 352Dmm