

# E dur SERIES



E dur-915



E dur-915S



E dur-916SU

A premium microphone collection, the E dur Series is designed for exceptional professional performance. The cutting edge capsule is mounted in our innovative shock-mount system and is equipped with a silent switch to ensure minimum handling noise. Great for all professional venues and events.

## E dur-915 (p.09)

*Live Stage Performance Microphone*  
Wired Microphone

**Polar Pattern:** Supercardioid  
**Frequency Response:** 50Hz~18KHz  
**Impedance:** 300Ω ± 30%  
**Sensitivity:** -75 ± 3dBV/μbar  
**Dimension (mm):** ø49 x 182  
**Weight (without cable):** 270 ± 10g



## E dur-915S (p.09)

*Live Stage Performance Microphone*  
Wired Microphone

**Polar Pattern:** Supercardioid  
**Frequency Response:** 50Hz~18KHz  
**Impedance:** 300Ω ± 30%  
**Sensitivity:** -75 ± 3dBV/μbar  
**Dimension (mm):** ø49 x 182  
**Weight (without cable):** 273 ± 10g



## E dur-916 (p.09)

*Live Stage Performance Microphone*  
Wired Microphone

**Polar Pattern:** Supercardioid  
**Frequency Response:** 50Hz~18KHz  
**Impedance:** 300Ω ± 30%  
**Sensitivity:** -74 ± 3dBV/μbar  
**Dimension (mm):** ø52.5 x 182  
**Weight (without cable):** 270 ± 10g



## E dur-916S (p.09)

*Live Stage Performance Microphone*  
Wired Microphone

**Polar Pattern:** Supercardioid  
**Frequency Response:** 50Hz~18KHz  
**Impedance:** 300Ω ± 30%  
**Sensitivity:** -74 ± 3dBV/μbar  
**Dimension (mm):** ø52.5 x 182  
**Weight (without cable):** 273 ± 10g



## E dur-916SU (p.27)

*Home Studio Microphone*  
Wired Microphone

**Polar Pattern:** Supercardioid  
**Frequency Response:** 50Hz~18KHz  
**Impedance:** 300Ω ± 30%  
**Sensitivity:** -74 ± 3dBV/μbar  
**USB Standard:** USB 2.0/Full-Speed 12 Mbps  
**Sampling Rate:** 48KHz/16 bits  
**Weight (without cable):** 270 ± 10g  
**Dimension (mm):** ø52.5 x 182



E dur-916

E dur-916S