



High-Definition CRT Display Applications


Features

- High f_T (Gain-Bandwidth Product).
- Small reverse transfer capacitance ($C_{re}=1.3\text{pF}$).
- Adoption of FBET process.

Package Dimensions

unit:mm

2006A



Specifications

Absolute Maximum Ratings at $T_a = 25^\circ\text{C}$

| Parameter | Symbol | Conditions | Ratings | Unit |
|------------------------------|-----------|------------|-------------|------------------|
| Collector-to-Base Voltage | V_{CB0} | | -70 | V |
| Collector-to-Emitter Voltage | V_{CEO} | | -60 | V |
| Emitter-to-Base Voltage | V_{EBO} | | -4 | V |
| Collector Current | I_C | | -50 | mA |
| Collector Current (Pulse) | I_{CP} | | -100 | mA |
| Collector Dissipation | P_C | | 900 | mW |
| Junction Temperature | T_J | | 150 | $^\circ\text{C}$ |
| Storage Temperature | T_{stg} | | -55 to +150 | $^\circ\text{C}$ |

Electrical Characteristics at $T_a = 25^\circ\text{C}$







| Parameter | Symbol | Conditions | Ratings | | | Unit |
|---|---------------------|--|---------|-----|--------|---------------|
| | | | min | typ | max | |
| Collector Cutoff Current | I_{CBO} | $V_{CB}=-40\text{V}, I_E=0$ | | | (-)0.1 | μA |
| Emitter Cutoff Current | I_{EBO} | $V_{EB}=-3\text{V}, I_C=0$ | | | (-)1.0 | μA |
| DC Current Gain | h_{FE} | $V_{CE}=-10\text{V}, I_C=-10\text{mA}$ | 60* | | 320* | |
| Gain-Bandwidth Product | f_T | $V_{CE}=-10\text{V}, I_C=-10\text{mA}$ | 350 | 700 | | MHz |
| Base-to-Collector Time Constant | τ_{bb}, τ_c | $V_{CE}=-10\text{V}, I_C=-10\text{mA}$ | | 8 | | |
| Output Capacitance | C_{ob} | $V_{CB}=-10\text{V}, f=1\text{MHz}$ | | 1.7 | | pF |
| Reverse Transfer Capacitance | C_{re} | $V_{CB}=-10\text{V}, f=1\text{MHz}$ | | 1.3 | | pF |
| Collector-to-Emitter Saturation Voltage | $V_{CE(sat)}$ | $I_C=-20\text{mA}, I_B=-2\text{mA}$ | | | -0.6 | V |
| Base-to-Emitter Saturation Voltage | $V_{BE(sat)}$ | $I_C=-20\text{mA}, I_B=-2\text{mA}$ | | | -1.0 | V |
| Collector-to-Base Breakdown Voltage | $V_{(BR)CBO}$ | $I_C=-10\mu\text{A}, I_E=0$ | -70 | | | V |
| Collector-to-Emitter Breakdown Voltage | $V_{(BR)CEO}$ | $I_C=-1\text{mA}, R_{BE}=\infty$ | -60 | | | V |
| Emitter-to-Base Breakdown Voltage | $V_{(BR)EBO}$ | $I_E=-10\mu\text{A}, I_C=0$ | -4 | | | V |

* : The 2SA1433 is classified by 10mA h_{FE} as follows :

| | | | | | | | | |
|----|---|-----|-----|---|-----|-----|---|-----|
| 60 | D | 120 | 100 | E | 200 | 160 | F | 320 |
|----|---|-----|-----|---|-----|-----|---|-----|

 h_{FE} rank : D, E, F

2SA1433



■ No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.

■ Anyone purchasing any products described or contained herein for an above-mentioned use shall:

- ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use;
- ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.

■ Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

This catalog provides information as of July, 1998. Specifications and information herein are subject to change without notice.

This datasheet has been download from:

www.datasheetcatalog.com

Datasheets for electronics components.