

1505A Coax - RG-59/U Type

		<p style="text-align: center;">For more information please call 1-800-Belden1</p> <p style="text-align: center;"><u>See Put-ups and Colors</u></p>
---	--	--

Description:

20 AWG solid .032" bare copper conductor, gas-injected foam HDPE insulation, Duofoil® + tinned copper braid shield (95% coverage), PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Coax	1
Total Number of Conductors	1
RG Type	59/U
AWG	20
Stranding	Solid
Conductor Diameter	.032 in.
Conductor Material	BC - Bare Copper

INSULATION:

Insulation Material	Gas-injected FHDPE - Foam High Density Polyethylene
Insulation Diameter	.145 in.

OUTER SHIELD:

Outer Shield Material Trade Name	Duofoil®
Outer Shield Type	Tape/Braid

Outer Shield Material :

Layer Number	Trade Name	Type	Material	% Coverage (%)
1	Duofoil®	Tape	Aluminum Foil-Polyester Tape-Aluminum Foil	100
2		Braid	TC - Tinned Copper	95

Outer Shield % Coverage	100 %
-------------------------	-------

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
-----------------------	--------------------------

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.233 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-30°C To +75°C
UL Temperature Rating	75°C

1505A Coax - RG-59/U Type

Bulk Cable Weight	31 lbs/1000 ft.
Max. Recommended Pulling Tension	47 lbs.
Min. Bend Radius (Install)	2.5 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CMR
CEC/C(UL) Specification	CMG
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2005

FLAME TEST:

UL Flame Test	UL1666 Vertical Shaft
---------------	-----------------------

SWEEP TEST:

Sweep Testing	100% Sweep tested 5 MHz to 4.5 GHz.
---------------	-------------------------------------

SUITABILITY:

Suitability - Indoor	Yes
Suitability - Outdoor	Yes - Black only
Suitability - Aerial	Yes - Black only, when supported by a messenger wire

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
Plenum Number	1506A

ELECTRICAL CHARACTERISTICS:

Nom. Characteristic Impedance	75 Ohms
Nom. Inductance	0.107 μ H/ft
Nom. Capacitance Conductor to Shield	16.3 pF/ft
Nominal Velocity of Propagation	83 %
Nominal Delay	1.22 ns/ft
Nom. Conductor DC Resistance @ 20 Deg. C	10.0 Ohms/1000 ft
Nominal Outer Shield DC Resistance @ 20 Deg.C	3.8 Ohms/1000 ft

Minimum Return Loss :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Minimum Return Loss (dB)
		5	1600	23
		1600	4500	21

Nom. Attenuation :

1505A Coax - RG-59/U Type

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Nom. Attenuation (dB/100 ft.)
	1			.3
	3.6			.6
	5			.63
	7			.74
	10			.9
	67.5			2.05
	71.5			2.1
	88.5			2.2
	100			2.3
	135			2.7
	143			2.8
	180			3.1
	270			3.8
	360			4.4
	540			5.5
	720			6.4
	750			6.5
	1000			7.6
	1500			9.3
	2000			10.9
	2250			11.6
	3000			13.4
	4500			16.4

Max. Operating Voltage - UL	300 V RMS
Other Electrical Characteristic 1	Impedance tested in accordance with ASTM D-4566 paragraph 43.2, option 2 using a 75 Ohm fixed bridge and termination. 75 +/- 1.5 Ohms
Other Electrical Characteristic 2	Return Loss tested in accordance with ASTM D-4566 paragraph 45.3, using a 75 Ohm fixed bridge and termination.

NOTES:

Notes	Also available in bundled versions. See 7794A through 7798A.
-------	--

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
1505A N3U1000	#20 PE/GIFHDPE SH FR PVC	1000	35	GREEN, MIL	C
1505A 0011000	#20 PE/GIFHDPE SH FR PVC	1000	35	BROWN	C
1505A 0021000	#20 PE/GIFHDPE SH FR PVC	1000	35	RED	C
1505A 002500	#20 PE/GIFHDPE SH FR PVC	500	15.5	RED	C
1505A 0031000	#20 PE/GIFHDPE SH FR PVC	1000	35	ORANGE	C
1505A 0041000	#20 PE/GIFHDPE SH FR PVC	1000	35	YELLOW	C

1505A Coax - RG-59/U Type

1505A 0061000	#20 PE/GIFHDPE SH FR PVC	1000	35	BLUE, LIGHT	C
1505A 006500	#20 PE/GIFHDPE SH FR PVC	500	15.5	BLUE, LIGHT	C
1505A 0071000	#20 PE/GIFHDPE SH FR PVC	1000	35	VIOLET	C
1505A 0081000	#20 PE/GIFHDPE SH FR PVC	1000	35	GRAY	C
1505A 0091000	#20 PE/GIFHDPE SH FR PVC	1000	35	WHITE	C
1505A 0101000	#20 PE/GIFHDPE SH FR PVC	1000	35	BLACK	C
1505A 010500	#20 PE/GIFHDPE SH FR PVC	500	15.5	BLACK	C
1505A N3U5000	#20 PE/GIFHDPE SH FR PVC	5000	165	GREEN, MIL	C N
1505A 0015000	#20 PE/GIFHDPE SH FR PVC	5000	165	BROWN	C N
1505A 0025000	#20 PE/GIFHDPE SH FR PVC	5000	165	RED	C N
1505A 0035000	#20 PE/GIFHDPE SH FR PVC	5000	165	ORANGE	C N
1505A 0045000	#20 PE/GIFHDPE SH FR PVC	5000	165	YELLOW	C N
1505A 0065000	#20 PE/GIFHDPE SH FR PVC	5000	165	BLUE, LIGHT	C N
1505A 0075000	#20 PE/GIFHDPE SH FR PVC	5000	165	VIOLET	C N
1505A 0085000	#20 PE/GIFHDPE SH FR PVC	5000	165	GRAY	C N
1505A 0095000	#20 PE/GIFHDPE SH FR PVC	5000	165	WHITE	C N
1505A 0105000	#20 PE/GIFHDPE SH FR PVC	5000	165	BLACK	C N

C = CRATE REEL PUT-UP.

N = FINAL PUT-UP LENGTH MAY VARY -0% TO +10% FROM LENGTH SHOWN.

Revision Number: 6 Revision Date: 09-07-2006

1505A Coax - RG-59/U Type

© Copyright 2006 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.