

## Bulk Cables | Microphone Cable

balanced

### **NEW!** SOMMER CABLE - SC-STAGE 22 HIGHFLEX

 **stage**  **mobile**  **Installation**

**ANALOG**

**OFC**

#### *One thick coat...*

will protect the interior against mechanical wear, eg. pulling, tugging, and knotting. For this reason we equipped the STAGE 22 with a thick outer jacket of 6.4 mm. Also the electrical data and the technical construction are worth taking a look at: The STAGE 22 offers low capacity and high bending cycles, this is provided by the fine and dense individual stranding.

The shielding made of polished copper wires is 99 % optically opaque (instead of the usual 85 %). Thus the STAGE 22 is the ideal cable for stage, home recorder, the leasing agent, and the installation technician.

The STAGE 22 is a very affordable cable with no need to compromise.

#### THE ADVANTAGES:

- High transmission quality due to the use of fine stranding
- Very robust due to the thick, soft PVC-jacket
- Good protection due to the dense copper spiral shielding
- High flexibility makes it easy to wind
- Very affordable price

#### THE APPLICATION:

- Stage application
- Home recording

#### TECHNICAL DATA:

Construction	(2LI2Y0,22mm <sup>2</sup> )DY
Jacket, diameter	PVC 6,4 mm
AWG	24
No. of inner conductors	2 x 0,22 mm <sup>2</sup>
Copper strand per conductor	32 x 0,10 mm
Conductor insulation	PE 1,40 mm
Shielding	copper spiral shielding with 0.10 mm indiv. strand
Shielding factor	99 %
Temperature range	min. -20 °C
Temperature range	max. 70 °C
Fire load per m	0,22 kWh
Weight per 1 m	55 g
Packaging	100/500 m roll

Color ■ purple

---

**ELECTRICAL DATA:**

---

Capac. cond./cond. per 1 m	68 pF
Capac. cond./shield. per 1 m	130 pF
Cond. resistance per 1 km	53 Ohm
Shield. resistance per 1 km	25 Ohm
Insulation resist. per 1 km	> 1 GOhm
Impedance	approx. 100 Ohm

---

**ORDER DATA:**

---

Order No.	200-0008
Rec. price	on request

---



---

v2008-JUN-8