

## AC/DC Digital Clamp Meters

MODEL **2010**

▶ Selection Guide

- High sensitivity, miniature AC/DC clamp meter.
- 0.1mA minimum resolution for AC current and 1mA minimum resolution for DC current.
- Output terminal for recorder connection.

Φ7.5    MAX AC/DC20A    OUT PUT  
External Power Supply



AC A	200mA/2/20A ±1%rdg±2dgt [50/60Hz] (200mA) ±1.5%rdg±4dgt [40Hz~2kHz] (200mA) ±1%rdg±2dgt [50/60Hz] (2A) ±2.5%rdg±5dgt [40Hz~2kHz] (2/20A)
DC A	2/20A ±1%rdg±2dgt (2A) ±1.5%rdg±4dgt (20A)
Output Voltage	200mV DC for 200mA AC/DC and 2A/20A AC/DC full scale
Conductor Size	Ø7.5mm max.
Frequency Response	DC, 40Hz~2kHz
Withstand Voltage	750V AC for 1 minute
Power Source	6LF22(9V) × 1 or AC Adaptor
Dimensions	142(L) × 64(W) × 26(D)mm 153(L) × 23(W) × 18(D)mm Clamp Sensor
Weight	220g approx.
Accessories	9071(Carrying Case) Alkaline 6LF22 × 1 Instruction Manual
Optional	8022(AC Adaptor)(110V) 8023(AC Adaptor)(220V) 7014(Output Cord)