

# UT205/UT206



UT205



UT206

### SPECIFICATIONS

Basic Functions	Range	Best Accuracy	
		UT205	UT206
DC Voltage	400mV/4V/40V/400V/600V	±(0.8%+1)	±(0.8%+1)
AC Voltage	4V/40V/400V/600V	±(1.2%+5)	±(1.2%+5)
AC Current	400A/1000A	±(2%+5)	±(2%+5)
Resistance	400Ω/4kΩ/40kΩ/400kΩ/4MΩ/40MΩ	±(1%+2)	±(1%+2)
Capacitance	4nF/40nF/400nF/4μF/40μF/200μF	±(3%+5)	±(3%+5)
Temperature (°C)	-40°C~1000°C		±(1%+3)
Frequency	10Hz~10MHz	±(0.1%+3)	±(0.1%+3)
Duty Cycle	0.1%~99.9%	✓	✓
Special Functions			
Auto Ranging		✓	✓
Diode		✓	✓
Continuity Buzzer		✓	✓
Relative Mode		✓	✓
Data Hold		✓	✓
Display Backlight		✓	✓
Full Icon Display		✓	✓
Sleep Mode		✓	✓
Jaw Opening Light		✓	✓
Max. Jaw Size	40mm	✓	✓
Low Battery Display		✓	✓
Input Impedance for DC Voltage Measurement	Around 10MΩ	✓	✓
Max. Display	3999	✓	✓

### GENERAL CHARACTERISTICS

Power	9V Battery (6F22), 3V Battery (AAA x 2)
LCD Size	52 x 27 mm
Product Colour	Body - Grey Jaw - Red
Product Net Weight	530g (excluding tool box)
Product Size	260 x 90 x 45 mm
Standard Accessories	<b>UT205</b> - Test Lead, Batteries, English Manual, Test Clip, Tool Box <b>UT206</b> - Test Lead, Batteries, English Manual, Point Contact Temperature Probe, Test Clip, Tool Box
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	20 pcs
Standard Carton Measurement	591 x 370 x 474 mm (0.104 CBM Per Standard Carton)
Standard Carton Gross Weight	29kg