

# UNI-T<sup>®</sup> UT320 SERIES

## Contact Type Thermometers

UT321 • UT322 • UT323 • UT325



■ UT321



■ UT322



■ UT323



■ UT325

### SPECIFICATIONS



Specifications	Range	Best Accuracy				
Model		UT321	UT322	UT323	UT325	
Single or Dual Input		Single	Dual	Single	Dual	
Temperature	Type K	-200°C ~1372°C(-328°F~2501°F)	±(0.5%+0.8)	±(0.5%+0.8)	±(0.2%+0.6)	±(0.2%+0.6)
	Type J	-210°C ~1200°C(-346°F~2192°F)	±(0.5%+0.8)	±(0.5%+0.8)	±(0.2%+0.6)	±(0.2%+0.6)
	Type T	-250°C ~400°C(-418°F~752°F)	±(0.5%+0.8)	±(0.5%+0.8)	±(0.2%+0.6)	±(0.2%+0.6)
	Type E	-150°C ~1000°C(-238°F~1832°F)	±(0.5%+0.8)	±(0.5%+0.8)	±(0.2%+0.6)	±(0.2%+0.6)
	Type R	0.0°C ~1767°C(+32°F~3212°F)			±(0.2%+2)	±(0.2%+2)
	Type S	0.0°C ~1767°C(+32°F~3212°F)			±(0.2%+2)	±(0.2%+2)
	Type N	-200°C ~1300°C(-328°F~2372°F)			±(0.2%+1.5)	±(0.2%+1.5)
Resolution	0.1°C (When Value>999.9°C:1°C)	✓	✓	✓	✓	
<b>Features</b>						
°C/°F/K Selection		✓	✓	✓	✓	
Data Hold		✓	✓	✓	✓	
Auto Power Off		✓	✓	✓	✓	
Low Battery Indication		✓	✓	✓	✓	
MAX Mode		✓	✓	✓	✓	
MIN Mode		✓	✓	✓	✓	
AVG Mode		✓	✓	✓	✓	
Data Logging		100	100	100	100	
USB Interface		✓	✓	✓	✓	
High Alarm				✓	✓	
Low Alarm				✓	✓	
High/Lower Signal Output				✓	✓	
LCD Backlight		✓	✓	✓	✓	
Auto Calibration				✓	✓	
Electricity Cut-off Memory		✓	✓	✓	✓	

### GENERAL CHARACTERISTICS

Power	USB or 9V Battery (6F22)
LCD Size	30mm × 32mm
Product Color	Red and Grey
Product Net Weight	270g
Product Size	175mm × 85mm × 30mm
Standard Accessories	Battery, USB Interface Cable, PC Software CD, Type K Temperature Probe
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	40 PCs
Standard Carton Measurement	460mm × 390mm × 270mm (0.048 CBM Per Standard Carton)
Standard Carton Gross Weight	21 Kg