

UT39A/UT39B

STANDARD DIGITAL MULTIMETERS



UT39A



UT39B

SPECIFICATIONS

Basic Functions	Range	Best Accuracy	
		UT39A	UT39B
DC Voltage	200mV/2V/20V/200V/1000V	$\pm(0.5\%+1)$	$\pm(0.5\%+1)$
AC Voltage	2V/20V/200V/750V	$\pm(0.8\%+3)$	$\pm(0.8\%+3)$
DC Current	20 μ A/200 μ A/2mA/20mA/200mA/10A 20 μ A/2mA/20mA/200mA/10A	$\pm(0.8\%+1)$	$\pm(0.8\%+1)$
AC Current	200 μ A/20mA/200mA/10A 2mA/200mA/10A	$\pm(1\%+3)$	$\pm(1\%+3)$
Resistance	200 Ω /2k Ω /20k Ω /200k Ω /2M Ω /200M Ω 200 Ω /2k Ω /20k Ω /2M Ω /20M Ω /200M Ω	$\pm(0.8\%+1)$	$\pm(0.8\%+1)$
Capacitance	2 μ F 2nF/200nF/20 μ F	$\pm(4\%+3)$	$\pm(4\%+3)$

Special Functions

Diode		✓	✓
Continuity Buzzer		✓	✓
Transistor		✓	✓
Sleep Mode		✓	✓
Low Battery Display		✓	✓
Input Impedance for DC Voltage Measurement	Around 10M Ω	✓	✓
Max. Display	1999	✓	✓

GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	61 x 32 mm
Product Colour	UT39A/UT39B - Grey Hoister - Red
Product Net Weight	3:0g (including Hoister)
Product Size	:72 x 83 x 38 mm
Standard Accessories	Test Lead, Battery, English Manual; Hoister
Standard individual Packing	Gift Box
Standard Quantity Per Carton	40 pcs
Standard Carton Measurement	598 x 4:8 x 340 mm (0.085 CBM Per Standard Carton)
Standard Carton Gross Weight	2:kg