


[Enlarge](#)

[Download Manual](#)
[Download Software](#)

SPECIFICATIONS

| Basic Functions | Range | Best Accuracy |
|---|--|---------------|
| DC Voltage | 200mV/2V/20V/200V/1000V | ± (0.1%+8) |
| AC Voltage | 2V/20V/200V/1000V | ± (0.8%+40) |
| DC Current | 200µA/2000µA/20A/200mA/10A | ± (0.2%+15) |
| AC Current | 200µA/2000µA/20A/200mA/10A | ± (1%+15) |
| Resistance | 200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ | ± (0.5%+20) |
| Capacitance | 20nF/200nF/2µF/20µF/200µF/2mF/20mF | ± (1.5%+20) |
| Frequency | 20Hz/200Hz/2kHz/20kHz/200kHz/2MHz/20MHz/200MHz | ± (0.1%+15) |
| Duty Cycle | 10%~90% | ± (1%+30) |
| Special Functions | | |
| Fused 10A Range | | ✓ |
| Auto Ranging | | ✓ |
| Current Measurement Alarm | | ✓ |
| Function Set Up | | ✓ |
| Voltage & Current : AC + DC Measurement | | ✓ |
| Diode | | ✓ |
| Continuity Buzzer | | ✓ |
| True RMS | | ✓ |
| Peak Hold | | ✓ |
| Max/Min Mode | | ✓ |
| Relative Mode | | ✓ |
| Data Hold | | ✓ |
| USB | | ✓ |
| Double Display Backlight | | ✓ |
| Full Icon Display | | ✓ |
| Sleep Mode | | ✓ |
| Low Battery Display | | ✓ |
| Input Impedance for DC Voltage Measurement | DC 200mV : Around 2.5GΩ All Other Ranges : 10MΩ | ✓ |
| Max. Display | 20000 | ✓ |
| Analogue Bar Graph | | ✓ |

GENERAL CHARACTERISTICS

| | |
|---------------------------------|--|
| Power | 9V Battery (6F22) |
| LCD Size | 73 x 50 mm |
| Product Colour | Red and Grey |
| Product Net Weight | 384g |
| Product Size | 200 x 93 x 40mm |
| Standard Accessories | Test Lead, Battery, English Manual, Alligator Clip, Test Clip, USB Interface Cable, Software, Carrying Bag |
| Optional Accessories* | Clip-On Test Lead Light (UT-TL), Built-In Test Lead Light (UT-L1), Built-In Test Lead Light Plus (UT-L2) |
| Standard Individual Packing | Gift Box |
| Standard Quantity Per Carton | 20 pcs |
| Standard Carton Measurement | 542 x 376 x 388mm (0.079 CBM Per Standard Carton) |
| Standard Carton Gross Weight | 19kg |

[Back to main menu](#)