



Print photo +  
datasheet



# DUAL THERMOMETER

Model : TM-906A

FEATURES	
* Microprocessor circuit assures maximum possible accuracy, provides special functions and features.	* RS 232 PC serial interface.
* Super large LCD display with contrast adjustment for best viewing angle.	* Multi functions, dual channel temp. input, differential temp. measurement, °C/°F, 0.1/1 degree, data hold.
* Dual function meter's display.	* Wide measuring range from -50 °C to 1230 °C.
* Heavy duty & compact housing case.	* Meet any standard type K(NiCr-NiAl) probe.
* Records Maximum and Minimum readings with RECALL.	* Fitted with standard type K thermocouple input measuring socket.
* Data hold.	* Build in temperature linearity & precision cold junction compensation circuit, high accuracy.
* Auto shut off saves battery life.	* Low battery indicator.
* Operates from 006P DC 9V battery.	

GENERAL SPECIFICATIONS			
Circuit	Custom one-chip of micro-processor LSI circuit.	Memory Recall	Records Maximum and minimum readings with RECALL.
Display	* 13 mm(0.5") Super large LCD display with contrast adjustment for best viewing angle. * Dual function meter's display.	Power off	Auto shut off saves battery life. or manual off by push button.
		Sampling Time	Approx. 0.8 to 1.0 second.
Sensor Type	Thermocouple K(NiCr-NiAl).	Operating Temp.	0 °C to 50 °C(32 °F to 122 °F).
Measurement	Two channel temp. input (T1, T2), differential temperature measurement(T1 -T2), °C/°F, 0.11 data hold.	Operating Humidity	Less than 80% R.H.
		Power Supply	006P DC 9V battery. (Heavy Duty Type)
Range	- 50 °C to 1230 °C, - 50 °F to 1999 °F.	Power Current	Approx. DC 6.2 mA.
		Weight	275 g/0.61 LB.
Polarity	Automatic switching, '-' indicates negative polarity.	Dimension	180 x 72 x 32 mm. (7.1 x 2.8 x1.3 inch).
Input Impedance	10 Mega ohm.	Accessories	Instruction manual.....1 PC. Sensor probe, TP-01.....1 PC.
Over input indication	Indication of " - - - ".	Optional Accessories	Temperature probe. Carrying case.
Data Output	RS 232 PC serial interface.		

ELECTRICAL SPECIFICATIONS (23 ± 5 °C)			
	TEMP. RANGE	RESOLUTION	ACCURACY
°C	-50 °C to 1230 °C	0.1 °C	-50 °C to 199.9 °C : ±(0.3% + 1 °C)
		1 °C	-50 °C to 1000 °C : ±(0.3% + 1 °C) 1001 °C to 1230 °C ±(0.5% + 1 °C)
°F	-50 °F to 1999 °F	0.1 °F	-50 °F to 199.9 °F : ±(0.3% + 2 °F)
		1 °F	-50 °F to 1999 °F : ±(0.3% + 2 °F)
°C	T1 - T2		±(0.3% + 2 °C)
°F	T1 - T2		±(0.3% + 3 °F)

\* The above accuracy specification applies only to the instrument itself and allowance must be made for limits of error permitted in thermocouple.

OPTIONAL TEMPERATURE PROBE & OTHER ACCESSORIES	
Thermocouple Probe (Type K) TP-01	Measure Range: -40 °C to 250 °C, -40 °F to 482 °F Max. short-term operating Temperature: 300 °C (572 °F). It is an ultra fast response naked-bead thermocouple, suitable for many general purpose application.
Thermocouple Probe (Type K), TP-02A	Measure Range: -50 °C to 900 °C (-50 °F to 1650 °F). Dimension: 10cm tube, 3.2mm Dia.
Thermocouple Probe	Measure Range: -50 °C to 1200 °C (-50 °F to 2200 °F)

[ [Previous page](#) ] [ [Product-index](#) ] [ [Model-index](#) ] [ [New products](#) ]