

CENTER 200 SERIES MINI CLAMP METER



- **AC/DC Current(201)**
- **Pocket Size**
- **High Speed Bargraph**
- DATA HOLD Function
- Touch ZERO Function (201)
- Auto Power Off
- Autoranging
- Measuring Frequency From Current Clamp & Test Terminal



CE IEC 1010 300V CATIII
600V CATII

CENTER®

GENERAL SPECIFICATIONS


Numerical Display:

3-3/4 digital liquid crystal display(LCD), Maximum reading 3999.

Battery Life:

200hr approx. (CENTER 200) 50hr approx. (CENTER 201)

Low Battery Indication:

The  is displayed.

Sampling Rate:

Digital:2 Times/sec ; Analog Bargraph:20 Times/sec

Power Source:

1.5V, Size AAA battery × 2

Auto Power Off:

30 minute

Operating Temperature and Humidity:

0°C to 40°C (32°F to 104°F) below 80%RH

Storage Temperature and Humidity:

-10°C to 60°C (14°F to 140°F) below 70%RH

Dimensions: (L)× (W)× (H)

193×50×28mm ; 7.60"×1.97"×1.10"

Weight:

Approx.240g

Jaw Opening Diameter:

Cables 25mm(CENTER 200) Cables 30mm(CENTER 201)

Accessories:

Carrying case, Battery, Instruction Manual & Test Lead

ELECTRICAL SPECIFICATIONS

Function	Range	Resolution	Accuracy
ACA	40A	0.01A	±1.9%rdg+5dgt(200)
	400A	0.1A	±2.0%rdg+5dgt(201)
DCA	40A	0.01A	±2.5%rdg+5dgt
	400A	0.1A	
ACV	400V	0.1V	±1.5%rdg+5dgt
	600V	1V	
DCV	400V	0.1V	±1%rdg+5dgt
	600V	1V	
Ohm	400 Ω	0.1 Ω	±1%rdg+2dgt
·))	·))	Active Sound Level: ≤ 40 Ω	
Hz(A)	4KHz	1Hz	±0.1%rdg+1dgt
	10KHz	10Hz	
Hz(V)	4KHz	1Hz	±0.1%rdg+1dgt
	40KHz	10Hz	
	400KHz	100Hz	
	1MHz	1KHz	



**ACTUAL SIZE
1 : 1**

CENTER®

CENTER TECHNOLOGY CORP.

4/F., No.415, Jung-Jeng Rd., 238 Shu-Lin Chien, Taipei, Taiwan
 TEL: 886-2-26763926 E-Mail: center@centertek.com
 FAX: 886-2-26763925 http://www.centertek.com

Distributed by: