

Pocket type



PM11

Coming soon!

Tough but compact DMM

- 3-3 / 4 digits 4000 count
- 0.8% best accuracy
- Analog bar graph
- Compact storage of test leads
- Test lead can be snapped into a fixed position atop the case.

Display : numeral display 4000, bar graph 40 segments

Sampling rate : 1.3 times / sec., 13 times / sec.
for bar graph

AC frequency bandwidth : 45~1kHz

Safety : IEC61010-1 CAT. III 300V Max. / CAT. II 500V Max.



Function	Measuring range	Best accuracy	Resolution	Input impedance
DCV	400m/4/40/400/500V	± (0.8%+4)	0.1mV	DCV: 10M~ 100MΩ
ACV	4.0/40/400/500V	± (2.3%+8)	0.001V	ACV: 10M~ 11MΩ
Resistance	400/4.0k/40k/400k/4.0M/40M	± (2.0%+4)	0.1Ω	
Continuity	Buzzer sounds at less than 20Ω. Open voltage : approx. 1.3V			
Diode test	Open voltage : approx. 3V			
Bandwidth	45~1kHz			
Battery	Button battery LR-44X2			
Size / Weight	H117×W76×D18mm/approx. 117g			
Standard accessories included	Instruction manual			

Optional accessories

Clip adapter : CL-13