

CE



DCM2000AD (with case)

DC / AC current measurable max.
2000A & DMM functions

- DC / AC current measurable max. 2000A
- Auto power off (10min.)
- Data hold / Range hold

Display : numeral display 4000

Sampling rate : 2 times / sec.

AC frequency bandwidth : 50 / 60Hz

Safety : IEC61010-1 (EN61010-1) 2001-02 CAT. III 600V Max.

Optional accessories

Clip adapter : CL-11, TL-8IC, CL-15

Test lead : TL-21M



Function	Measuring range	Best accuracy	Resolution
ACA	40/400/2000A	± (1.5%+8)	0.01A
DCA	40/400/2000A	± (1.5%+8)	0.01A
ACV	400m/4/40/400/600V	± (1.2%+8)	0.1mV
DCV	400m/4/40/400/600V	± (1.2%+8)	0.1V
Resistance	400/4k/40k/400k/4000k/40MΩ	± (1.5%+8)	0.1Ω
Frequency	100/1k/10k/100k/1000kHz	± (0.5%+3)	0.1Hz
Continuity	Buzzer sounds at less than approx. 40Ω. Open voltage : approx. 1.5V		
Bandwidth	50/60Hz		
Display	4000		
Clamp diameter/ Conductor size	53mm/20×60mm		
Withstand voltage	5550VAC		
Battery	R03×2		
Size / Weight	H240×W84×D34mm/appox. 400g		
Standard accessories included	Test lead (TL-21) , Carrying case (C-DCM2000) , Instruction manual		