

AC/DC Digital Clamp Meters

MODEL **2004**

▶ Selection Guide

- Smallest clamp meter capable of AC and DC current measurements.
- 20A range has a minimum resolution of 0.01A AC/DC.
- AC/DC voltage and resistance measurement functions also available.



AC A	20/200A ±1%rdg±2dgt [50/60Hz] (20A) ±1.5%rdg±4dgt [40Hz~1kHz] (20A) ±1.5%rdg±4dgt [50/60Hz] (0~150A) ±2%rdg±5dgt [40Hz~1kHz] (0~150A) ±3.5%rdg [40Hz~1kHz] (>150A)
AC V	500V ±1.5%rdg±2dgt [50/60Hz] ±2%rdg±4dgt [40Hz~1kHz]
DC A	20/200A ±1%rdg±2dgt (20A) ±1.5%rdg±2dgt (0~150A) ±3%rdg (>150A)
DC V	200V ±1%rdg±2dgt
Ω	200Ω ±1.5%rdg±2dgt
Conductor Size	Ø19mm max.
Frequency Response	DC, 40Hz ~ 1kHz
Withstand Voltage	1000V AC for 1 minute
Power Source	R6P(AA)(1.5V) × 2
Dimensions	180(L) × 54(W) × 31(D)mm
Weight	170g approx.
Accessories	7066 (Test Leads) 9055(Carrying Case) R6P(AA) × 2 Instruction Manual
Optional	8004/8008 (Multi-Tran)(AC only) 8021 (Energizer)