

Description

This family of high power remote sensing, remote control, switching mode CC/CV power supply offers unique solution for various loading conditions and applications.

The remote control functionality makes

1. output on/off possible without turning the power on/off switch of the unit.
2. adjusting the output voltage and current without turning the controls of the unit.

The remote sensing capability is important for load away from the power supply or when load current becomes erratic.

It is ideal for applications that require precise voltage at the point of application

When using it as a normal bench power supply, the 10-turn potentiometers provide precise output voltage and current control. The 4 digit LED meters with clear indication of automatic cross over of CC and CV mode provide easy read outs.

With the optional accessory, unit can be easily converted to 19" rack mount construction in less than 5 minutes.

It is suitable for a wide range of applications such as production testing, laboratory, field test of voltage critical distant load, telecommunications, powering of dc network and etc.

Features

- Remote control for output power on-off .
- Remote control for voltage and current adjustment.
- Remote sensing for remote point of precise voltage regulation.
- Do It Yourself 19" Rack Mount with optional accessory.
- High RFI stability.
- CC & CV mode with auto-cross over.
- Output Over Voltage Protection.
- Active Power Factor Correction.
- Overload, Over-temperature, Short circuit Protections
- 10-turn wire wound potentiometers .
- 4 digit LED A and V meters.
- Thermally controlled variable speed fan.
- Universal Input 100-240VAC



Assembled with Do It Yourself
19" Rack Mount Front Panel



Specifications

	<i>SIM - 9106</i>	<i>SIM - 9303</i>
Variable Output Voltage	1 - 15Vdc	1 - 30Vdc
Variable Output Current	1 - 60A	1 - 30A
Load Voltage Regulation	0.1% +5mV	
Line Voltage Regulation	0.05% +3mV	
Load Current Regulation	0.2% +5mA	
Line Current Regulation	0.1% +5mA	
Ripple & Noise (Peak - Peak)	50mV p-p	
Ripple & Noise (r.m.s.)	<5mVrms	
Input Voltage	100 - 240Vac , 50 / 60Hz~	
Efficiency	≥82%	≥83%
Meter Type	LED Meter	
Voltmeter Range	4 digits - Display	
Ammeter Range	4 digits - Display	
Meter Accuracy	±0.5% +2 counts	
Protection Devices	Overload (Constant Current Limiting), Short Circuit, Over Temperature, OVP	
Cooling System	Variable Speed thermally Control Fan	
Special Feature	Remote Sensing, Remote Control	
Standard Accessory	Remote Control Plug, User Manual	
Optional Accessory	19" Rack Mount Kit (part no. SIM-9106 : 8781-9106-0000 / SIM-9303 : 8781-9303-0000)	
Approvals	CE EMC : EN 55011 , LVD : EN 61010	
Dimensions (WxHxD)	235 x 95 x 340mm / 9.3 x 3.8 x 13.4inch	
Weight	6kgs / 13.2lbs	
Remark	Power factor correction ≥0.97 at optional load	

All values are based on the Standard ambient Temperature 25°C and Pressure 0.1Mpa.

* SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE *