

S245 接點特效清洗潤滑劑 SUPER 10 Contact Cleaning Lubricant

SUPER 10 is a contact cleaning lubricant, formulated on a blend of aliphatic polyalcohols, inhibitor and solvent. It offers a combination of high purity electrical cleaning and mechanical lubrication for contacts, switches and relays.

APPLICATIONS

Removes grease, tarnish, oxidation and other contamination from contact surfaces and leaves a protective, conductive, lubricating film.

Cuts voltage drop between contacts by increasing the surface area and reducing resistance. The residual film resists drying and the attraction of dust. Eliminates contact bounce and stops the damage which can be caused by arcing between contacts. Improves the current flow and protects against friction.

Apply directly onto the components to be treated. **Ensure electrical equipment is switched off before applying SUPER 10.** After spraying, always leave for at least 4/5 minutes to allow dispersal of solvent vapours, before operating the equipment.

TECHNICAL DATA

Appearance	: Transparent liquid
Odour	: Solvent
SG @ 25°C	: 0.68
Pressure @ 25°C	: 3 Bar
Discharge rate	: 1.0 g/sec
Temperature range	: Operational up to 150°C
Solubility	: Soluble in most solvents, insoluble in water
Recommended solvents	: Amberklene FE10, ME20, L030 or Ambertron
Flammability	: Classified as extremely flammable under CHIP Regulations
Flashpoint	: Not applicable in sealed aerosol
Packaging	: 200 ml aerosol (12 per carton)