


Megapixel IP Camera

V6 Series Full HD • Real-time



Versatile H.264 IP Camera

Dimension



Unit: (mm)

Features

- Progressive Scan CMOS Sensor
- NEW** • Full HD 1080p / HD 720p real-time at dual streaming
- NEW** • H.264 and MJPEG compression
- Motion Detection
- Privacy Masks
- Day/Night (ICR)*
- Auto Iris Lens support*
- NEW** • Micro SD support*
- NEW** • BNC analog output*
- **C**onvif support


Note: Items marked with an asterisk (*) are optional

V1 Series Full HD • Real-time • Compact



Versatile H.264 IP Camera

Dimension



Unit: (mm)

Features

- Progressive Scan CMOS Sensor
- NEW** • Full HD 1080p / HD 720p real-time at dual streaming
- H.264 and MJPEG compression
- NEW** • f = 4 mm, F1.5
- Power over Ethernet (802.3af)
- Motion Detection
- Privacy Masks
- Weatherproof Dongle Cable*
- Weatherproof (IP66 international)
- Micro SD support*
- NEW** • Security Torx against tampering
- **C**onvif support

Megapixel IP Camera**V2 Series**


Full HD • Real-time • Vandal Proof




Versatile H.264 IP Camera

Dimension

Indoor



Outdoor



Unit: (mm)

Features

- Progressive Scan CMOS Sensor
- NEW** • Full HD 1080p / HD 720p real-time at dual streaming
- H.264 and MJPEG compression
- NEW** • Remote Zoom & Focus (Motorized Lens)*
- Motion Detection
- Privacy Masks
- Day/Night (ICR)
- NEW** • IR LED Module (effective distance: 20m)*
- NEW** • Micro SD support
- BNC analog output
- Weatherproof (IP66 international)
- NEW** • Vandal proof dome cover
- Sun Shield & Outdoor Mounting Kit
- **ONVIF** support



Note: Items marked with an asterisk (*) are optional

V3 Series

Full HD • Real-time • Vari-focal



Versatile H.264 IP Camera

Dimension


Unit: (mm)

Features

- Progressive Scan CMOS Sensor
- NEW** • Full HD 1080p / HD 720p real-time at dual streaming
- H.264 and MJPEG compression
- Remote Zoom & Focus (Motorized Lens)*
- NEW** • Lightweight dome cover
- Detachable modular design
- NEW** • 3-Axis position adjustment
- Motion Detection
- Privacy Masks
- Day/Night (ICR)
- NEW** • IR LED Module (effective distance: 20m)*
- Micro SD support
- **ONVIF** support

Megapixel IP Camera

Value Chart



Comparison Chart

Item	V1	V1 Rugged	V6	V3	V2
CMOS	●	●	●	●	●
Lens	fixed focal	fixed focal	C/CS mount	Manual VF	Motorized VF
ICR	-	-	○	○	●
Built-in Mic	○	-	-	-	○
Audio in	●	-	●	●	●
Audio out	-	-	●	●	●
Alarm	-	-	●	●	●
BNC	-	-	○	●	●
Micro SD	○	○	○	●	●
Weatherproof (IP66)	-	●	-	-	●

● Support ○ Optional - Not support

Specification

Item	Full HD Real-time	Full HD
Camera		
Image Sensor	1/2.7" Progressive CMOS	1/2.7" Progressive CMOS
Picture Elements	1920(H) × 1080(V)	1920(H) × 1080(V)
Shutter Speed	1~1/10000 sec.	1~1/10000 sec.
White Balance	Manual/ATW (1500 ~ 15000K)	Manual/ATW (1500 ~ 15000K)
Digital Zoom	Support	Support
Operation		
Video Compression	H.264 /MJPEG	H.264 /MJPEG
Video Streaming	Simultaneously, H.264 + H.264 Simultaneously, H.264 + MJPEG Simultaneously, MJPEG + BNC	Simultaneously, H.264 + H.264 Simultaneously, H.264 + MJPEG Simultaneously, MJPEG + BNC
Resolution	H.264: Full HD 1080p/HD 720p/D1/CIF MJPEG: Full HD 1080p/HD 720p/D1/CIF	H.264: Full HD 1080p/HD 720p/D1/CIF MJPEG: Full HD 1080p/HD 720p/D1/CIF
Frame Rate	H.264: 1080p 25/30fps MJPEG: 1080p 25/30fps	H.264: 720p 25/30fps MJPEG: 720p 25/30fps
Image Setting	Exposure, White Balance, Brightness, Sharpness, Contrast, Saturation, Hue, Image rotation, Motion detection, Privacy Mask	Exposure, White Balance, Brightness, Sharpness, Contrast, Saturation, Hue, Image rotation, Motion detection, Privacy Mask
Audio	Line Out, Line In/Mic In	Line Out, Line In/Mic In
Alarm	5V 10kΩ pull up	Photo relay output 300V DC/AC
Input		HTTP, FTP, SMTP
Output		English, French, German, Italian, Simplified Chinese
Event Notification		Internet Explorer (6.0+), Chrome, FireFox
Multiple Languages		20
Network		
Interface	RJ-45, 10/100 Mbps Ethernet	RJ-45, 10/100 Mbps Ethernet
Protocol	IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS, ONVIF	User and Administrator
Password Levels		HTTPS, IP Filter
Security		
Internet Browser		
User Account		
General		
Operating Temperature	0°C ~ 50°C (32°F ~ 122°F) Humidity: 10% to 90%, Non-condensing	0°C ~ 50°C (32°F ~ 122°F) Humidity: 10% to 90%, Non-condensing
Power Source	DC 12V / AC 24V / PoE	DC 12V / AC 24V / PoE
Power Consumption	4W+	4W+
Certificate	CE, FCC, RoHS compliant	CE, FCC, RoHS compliant

Product specification and availability subject to change without notice. Certain product names mentioned herein may be trade names and / or registered trademarks of their companies.

Product Selection



V6-

Solution A: Full HD CMOS B: Full HD CMOS, real-time	Lens Type 0: CS mount type 1: CS mount type, D/N	Power 2: DC 12V / PoE	Connectors 0: None 7: BNC & Auto Iris & Micro SD	Power Plug 0: None
--	---	---------------------------------	---	------------------------------



V1-

Solution A: Full HD CMOS B: Full HD CMOS, real-time	Lens Type 3: 6.0 mm, F1.6 4: 4.0 mm, F1.5	Power 4: PoE	Connectors 0: None 3: Mic & Micro SD	Ethernet 0: RJ-45 M: M12 R: RJ-45 Cable
--	--	------------------------	---	---



V2-

Solution A: Full HD CMOS B: Full HD CMOS, real-time	Lens Type A: Vari-focal B: Vari-focal 3.3 ~ 12 mm, D/N C: Motorized Vari-focal 3.3 ~ 12 mm, D/N	Power 3: DC 12V / AC 24V / PoE	IR LED 0: None 1: IR LED	Heater & Fan 0: Indoor B: Outdoor w/ H & F
--	---	--	---------------------------------------	---

*H & F: Heater & Fan



V3-

Solution A: Full HD CMOS B: Full HD CMOS, real-time	Lens Type A: Vari-focal B: Vari-focal 3.3 ~ 12 mm, D/N C: Motorized Vari-focal 3.3 ~ 12 mm, D/N	Power 3: DC 12V / AC 24V / PoE	IR LED 0: None 1: IR LED
--	---	--	---------------------------------------