

# MEDIA DVR

LR-804J03  
LR-804H05



LR-804J01



LR-804J02



## 3 in 1 MEDIA DVR

### DVR

- 4CH video input
- 4CH sensor input; 1CH alarm output
- Motion JPEG or H.264 compression
- Picture in picture

### PHOTO FRAME

- 8" high contrast TFT LCD display
- Built in SD/CF card reader







### Features

- ▶ 8" high contrast LCD display
- ▶ 4 CH video inputs Motion JPEG or H.264 compression
- ▶ 4 CH alarm sensor inputs ; 1 CH alarm output
- ▶ Video record resolution: 704x240 (704x288)(MJPEG Type)
- ▶ Picture in Picture/Multi-language OSD
- ▶ User friendly as operated PTZ by mouse directly
- ▶ Built in SD card, CF card and DVD player as media player or Photo frame
- ▶ SPOT monitor and video Loop function
- ▶ USB external backup or CD-RW backup
- ▶ Media out for external media display

## Specification

Model		LR-804J01	LR-804J02	LR-804J03	LR-804H05	
DVR	Video	Video Compression	MJPEG		H.264 compression	
		Video Input	4CH			
		Video Display	Full screen, 4 split screen, PIP, Sequence, Digital Zoom			
		Display Speed	Full motion: 30FPS(NTSC), 25(PAL)			
		Camera Configuration	Adjustable Camera ID and color			
	Recording	PTZ Control	Support PAN / TILT / ZOOM by using Mouse			
		Recording Rate	Max: 120FPS( NTSC ) ; 100FPS(PAL)		Max: 120FPS( NTSC ) ; 100FPS(PAL) @CIF	
		Recording Mode	Time Cyclic / Motion / Schedule / Alarm		Schedule / Continuous / Motion / Alarm	
		Recording Resolution	704 x 240 (NTSC) , 720 x 288 (PAL) 352 x 240 (NTSC) , 360 x 288 (PAL) (Default)		Quad Mode (4 CH/ D1). 720x480(NTSC) 720x576 (PAL)	
	Playback	Recording Quality	Lowest/ Low/ Normal/ High/ Highest		Low/ Normal/ High/ Highest	
		Playback Mode	Percent Search, Time/Date Search, Event Search			
		Playback Speed	Forward, Backward, 1X; 2X; 4X; 8X; 16X; 32X; 1/2X; 1/4X; 1/8X; 1/16X		Forward, Backward, 1X; 2X; 4X; 6X	
	Alarm	Sensor Input	4 (NO/NC Selectable)			
		Alarm Output	1 (NC)			
		Alarm Mode	Sensor input/ Video loss			
		Post Alarm	Alarm output duration : 1-99 Sec selectable			
		Pre Alarm	N/A		Pre Alarm: 5 Sec.	
		Motion Detect	Multiple configurable detection area and Mask			
	Storage	Event Spot	Switching Interval, Alarm Pop-Up, Motion Pop-Up, Event Pop-Up Duration			
		Internal Storage	3.5" IDE HDD (Hard disk Optional; Expandable up to 500 G)		3.5" SATA HDD	
Remote Backup		Download via IP Network				
Remote	Backup Device	CD-RW	USB mass-storage device (Backup; F/W Upgrade)		USB external device	
	Viewer	Remote live view, playback, backup, setting, PTZ control				
User Input Interface	Network	Ethernet (TCP/IP)				
	USB	Mouse				
	RS-485	For PTZ Camera Control				
	USB	N/A	1.For USB mouse 2.For mass-storage device or DVR FW upgrade		For mass-storage device or DVR FW upgrade	
	Network	RJ45				
LCD	Display	8" LCD Monitor				
	Resolution	800(H)×600(V)				
	Brightness	250 cd/m <sup>2</sup>				
	Contrast Ratio	500 : 1				
	Viewing Angel	70/70 (L/R) 70/70 (U/D)				
Media player	Media Video Storage	SD card, CF card	SD card	N/A	N/A	
	DVD Player	N/A	Yes	N/A	N/A	
Audio/Video interface	Video Input	BNC×4				
	Audio Input	N/A	N/A	N/A	RCA×4(DVR Audio)	
	Video Input Format	NTSC or PAL				
	Video Output	BNC×2 (Monitor/Spot)	BNC×2 (Monitor/Spot)	BNC×2 (Monitor/Spot)	BNC×1 (Monitor)	
	Audio Output	N/A	Phone-jack×1(Media Audio)	N/A	Phone-jack×1(DVR Audio)	
Others	Audio/Video Ouput	N/A	N/A	N/A	N/A	
	Operation Condition	60W (DC 12V/5A)				
	Power Supply	AC100-240 50/60Hz				
	Dimension	193(W)×182(H)×198(D) mm				
	Weight	3.32KG	3.44KG	2.86KG	2.87 KG	



Unit:mm

Specification is subject to change without notice. 2008.10



**TAIWAN VIDEO SYSTEM CO., LTD.**  
 3f-1., No.196, Xinhua 3rd Rd., Neihu District, Taipei City, Taiwan, R.O.C. 114  
 TEL: 02-8791-2600 FAX: 02-8791-9016  
 http://www.tvs.com.tw E-mail: info@tvs.com.tw

### TVS GROUP

USA TVSA e-mail: info@eversun.com  
 Germany TVSG e-mail: info@tvsg.de  
 China TVSC e-mail: info@tvsc.com.cn

